

SPECIFICATION

EBLS & EBLS/AP

- · Contacts: Changeover contacts
- Output: 10 AMP contact @ 240V AC/DC
- Printed pad legend
- · Fixing screws supplied
- Interal use only

Antibacterial Certified:

· All RGL EBLS range of white moulded exit buttons are manufactured using Urea Formaldehyde, which destroys 99.9% of MRSA, E-Coli, Salmonella and Klebsiella Pneumoniae

TO EXIT

EBLS/PTE

FEATURES

EBLS & EBLS/AP

- Retractable switch
- High impact plastic back box
- · Can be surface or flush fitting
- · Easy clean surface. Ideal for general/sensitive areas

EBLS/AP

· Screw footprint for flush fitting onto standard back box

Antiviral Certified:

CONTENTS

• Exit Button

Surface Box

· 2 Screws

EBLS & EBLS/AP

· All RGL EBLS range of white moulded exit buttons were shown to have a 99.9& kill off rate against enveloped viruses and a 92% kill off rate against non-enveloped viruses

DIMENSIONS

FBLS

- 85x85x28 (mm)
- ·140g (Boxed) ·120g (Unboxed)
- EBLS/AP
- 85x39x28 (mm)
- · 80g (Boxed) · 70g (Unboxed)



+44 (0)1902 656667

www.rgl.co





STE-P

DU-NT/TF

EBNT/TF-1

EBWLS/DR

510

info@rgl.co







