

# Market leading request to exit buttons, that are both hard wearing and cost effective. Suitable for use in applications where contactless options are a priority

# **TOUCH FREE EXIT DEVICE**

### HELPS STOP THE SPREAD OF GERMS







# **EBNT/TF-1**

### **SPECIFICATION**

### EBNT/TF-1

- · Contacts: Double pole NONC contacts
- · Contact Load: 0.5A @ AC 120V / 1A @ DC24V
- · Dual voltage 12/24 VDC @ 45mA operating
- · +/- 10% voltage tolerance
- · Etched legend (various options available)
- · Security screws (allen key type)
- · Button rated IP65 ingress protection
- · Adjustable relay opening times (0.5 to 20 sec)
- · Adjustable proximity distance (3 to 12 cm)
- $\cdot$  -10° to +70° operating temperature
- · Designed to prevent interference with other infra red devices

Requires a permanent power supply

- volt free contacts

### **FEATURES**

### EBNT/TF-1

- · 38mm Touch free sensor button
- · Illumination Green to red (or red to green)
- · High impact plastic back box
- · Can be surface or flush fitting
- · Easy clean surface
- · Ideal for general / sensitive areas
- · Screw footprint for flush fitting onto standard back box
- · Distance between fixing holes 60mm

Suitable Alternative Back Boxes

- · EXTR02 (Aluminium Extrusion 40mm)
- · SSBB02 (Stainless Steel Back Box 42mm)
- · PBB05 (Green or Black Back Box 40mm)

### **OTHER PRODUCTS**

1201SM-1





### **DIMENSIONS**

### EBNT/TF-1

- · 85x85x32 (mm)
- · 238g (Boxed)
- · 202g (Unboxed)

## **CONTENTS**

### FBNT/TF-1

- · Touch free button on SS Plate
- · Back box

- · Wires & connector
- · Screw bag
- · Instructions







Version 3.1





