

Email: info@totalsecuritytech.co.uk www.totalsecuritytech.co.uk





FUNCTION:

The button is designed to remove power from the circuit and turn the maglock off.

This product is ideal for use in areas where contactless operations are required

REX401

MOMENTARY SWITCH

TECHNICAL SPECIFICATIONS:

- Contacts: Double pole NONC contacts
- \cdot Contact Load: 0.5A @ AC 120V / 1A @ DC24V
- \cdot Dual voltage 12/24 VDC @ 45mA operating
- \cdot +/- 10% voltage tolerance
- · Etched legend (various options available)
- Security screws (allen key type)
- Button rated IP65 ingress protection

FEATURES:

- 38mm Touch free sensor button
- · Illumination Green to red (or red to green)
- High impact plastic back box
- · Can be surface or flush fitting
- Easy clean surface
- \cdot Ideal for general / sensitive areas
- Screw footprint for flush fitting onto standard back box
- Distance between fixing holes 60mm

```
REX401
85x85x28 (mm)
TOUCH FREE EXIT
232g (Boxed)
```

- · Adjustable relay opening times (0.5 to 20 sec)
- Adjustable proximity distance (3 to 12 cm)
- \cdot -10° to +70° operating temperature
- Designed to prevent interference with other infra red devices





Other items in the range:



Total I-Tech Ltd | 0121 270 5609 | info@totalsecuritytech.co.uk

REX401 - Exit Devices